



# Can the Linux kernel sustain 30 more years of growth? Toward mitigating bottlenecks in its development model

David Tadokoro  
Free Software Competence Center  
Institute of Mathematics and Statistics  
University of São Paulo  
São Paulo, SP, Brazil  
davidbtadokoro@usp.br

Rodrigo Siqueira  
Free Software Competence Center  
Institute of Mathematics and Statistics  
University of São Paulo  
São Paulo, SP, Brazil  
siqueirajordao@riseup.net

Paulo Meirelles  
Free Software Competence Center  
Institute of Mathematics and Statistics  
University of São Paulo  
São Paulo, SP, Brazil  
paulormm@ime.usp.br

## ABSTRACT

The Linux kernel, a cornerstone of modern computing and Free Software, forms the foundation of the GNU/Linux ecosystem and critical services like the Internet. Its development model integrates diverse workflows that extend beyond technical concerns. Despite its success, the project relies on key individuals and *ad-hoc* tools, raising sustainability and workforce renewal concerns. Moreover, known challenges within its development model remain underexplored in academic research. This paper presents ongoing efforts to develop taxonomies that describe these workflows, aiming to identify bottlenecks and guide the creation of Free Software tools to support the kernel long-term sustainability.

## KEYWORDS

GNU/Linux, Free Software, Open Source Software, Software Development Model, Software Engineering, Bottleneck Mitigation.

## 1 Introduction

Computers are essential devices that permeate modern life, from personal computers used for daily tasks to embedded systems in vehicles and industrial equipment performing critical functions. Although not strictly required, computers typically consist of two interacting components: hardware and software. Hardware refers to the physical elements, while software comprises the programs that control and direct hardware operations, taking various forms to do so.

A piece of software common in most types of computers (including some embedded systems) is an Operating System (OS). This typically vast and complex component serves as a bridge between software applications and hardware. According to *Silberschatz et al.* [13], “the operating system provides the means for proper use of these resources in the operation of the computer system. An operating system is similar to a government. Like a government, it performs no useful function by itself. It simply provides an environment within which other programs can do useful work.” The most important part of an OS is its kernel, which usually implements all core functionalities and manages hardware support through device drivers. *Silberschatz et al.* [13] also defines the kernel as “the one program running at all times on the computer.”

A prominent example of an OS kernel is the Linux kernel. Being Free Software, it can be fully modified and customized without licensing costs to meet the needs of individuals, companies, and government agencies. Supported by a broad and diverse community, Linux is central to the operating system ecosystem, underpins much of the Internet, and leads in fields like Machine Learning.

On the one hand, the Linux project continues to grow in size, complexity, and number of contributors, which can be viewed as continuously evolving and maturing. On the other hand, several concerns about its development model have been raised by both academia and practitioners: (i) scalability of the community and its workflows; (ii) workforce renewal; (iii) reliance on key individuals in critical, often irreplaceable, roles; (iv) inefficiencies and wasted community effort; (v) outdated technologies that remain core to the development process; (vi) *ad hoc* solutions to workflow bottlenecks and frequent duplication of effort.

More severely, academic studies on the Linux project often lack engagement with real-world practice and fail to investigate these concerns deeply, leading to homogeneous and biased perspectives [16]. Consequently, academic conclusions sometimes diverge significantly from the experiences reported in the Linux community (*grey literature*) and insights from close observation (*ethnographic case studies*) [16]. The widespread reliance on *ad hoc* solutions to common bottlenecks negatively impacts the scalability of both workflows and the workforce, threatening the project long-term sustainability. In-depth academic research that bridges state-of-the-art and state-of-practice could enable informed development of tools to support the Linux ecosystem and, by extension, the many critical services of society that rely on Linux.

Given this gap in academic understanding, many topics remain underexplored or superficially addressed in the literature. This work focuses on understanding the overarching kernel workflows (i.e., the processes and practices required to accomplish tasks) that define the Linux kernel development model. To that end, we are building a theoretical framework to describe these workflows and identify associated bottlenecks. Furthermore, we are designing and developing Free Software tools to help mitigate these bottlenecks, leveraging insights grounded in this framework.

While we recognize that achieving these objectives will not fully resolve all of the aforementioned issues, our objective is to establish a concrete and empirically grounded foundation upon which more comprehensive solutions can be built. Our approach is multi-method, with a strong emphasis on *ethnographic case studies* to remain close to practice, while also integrating academic literature, grey literature, and community insights to triangulate findings and strengthen their validity.

This paper outlines our ongoing efforts to bridge the gap between research and practice in the understanding of the Linux kernel development model. We aim to inspire further investigation and collaboration on sustainable, community-driven development of the tools that will help shape the next 30 years of Linux.

## 2 Background

The Linux kernel project is structured into interconnected subsystems analogous to neighborhoods in a city [16], each managed by maintainers responsible for overseeing developer contributions. These maintainers and their associated code base areas are listed in the MAINTAINERS file. However, entries in this file often overlap and share code, forming clusters rather than isolated entities, which more accurately represent subsystems [3]. Reflecting its distributed nature, the Linux community works in a decentralized, global, and asynchronous fashion. Despite the natural coupling between parts of the code base, each subsystem typically has a dedicated community and git repository (called *kernel tree*) with distinct governance, maintenance models, and domain-specific characteristics.

### 2.1 How the Linux kernel subsystems connect

The Linux kernel project operates like a city divided into neighborhoods (subsystems), each governed by maintainers and supported by their surrounding ecosystems. Each subsystem operates as an autonomous project with its dedicated kernel tree that synchronizes with the *mainline* (the kernel tree of Linus Torvalds, the creator of Linux) via pull requests<sup>1</sup>. These subsystems manage specific parts of the code base within a hierarchical *web of trust*, where responsibilities are delegated from higher to lower levels. Linus stands at the top as a *benevolent dictator* [1], resolving disputes and supervising the overall project direction. Despite this hierarchy, the structure is flatter than it appears: many maintainers submit pull requests directly to Linus, bypassing mid-level maintainers [2]. This recursive fragmentation of the top-level Linux project into smaller projects gives it scalability and allows for highly specialized personnel caring for every part of the code base.

However, some inefficiencies have been detected, such as 44% of contributions being ignored over the past decade [12], which can result in frustration and wasted community effort. This structure also makes the whole project reliant on key, often irreplaceable individuals, particularly Linus.

In other words, even though this “divide-and-conquer” approach has contributed to the Linux remarkable success, it exposes potential long-term risks, such as maintainer overload and project fragility due to reliance on critical personnel.

### 2.2 The Linux kernel development process

At the core of the Linux kernel development process is the *patch* - a text document that describes the difference between two versions of the source tree and represents a contribution to the project [16]. Like a git commit, a patch contains a code difference and a message, but it is formatted for email submission.

In the Linux project, mailing lists are the medium for all public communication. These mailing lists are hubs for development, bug reporting, and discussion. Contributors submit patches for review, and maintainers and peers provide feedback, initiating an iterative process known as the *patch-reviewing process*. This back-and-forth ensures high-quality contributions [11], and once a patchset (a collection of related patches) is accepted, it begins its path through the project hierarchical repository structure.

<sup>1</sup>A request to merge changes from one project fork into the original repository. Not to be confused with *GitHub Pull-Requests*.




Figure 1: Patches flow into the *mainline* [9].

Initially, patches are merged into the corresponding subsystem repository under the control of its maintainers. From there, they progress upward through the hierarchy until they are merged into the *mainline* repository. **Figure 1** illustrates this flow, highlighting the patch journey from contributor to mainline. To prevent regressions and ensure stability, *Continuous Integration* (CI) practices, such as temporary stabilization in the *-next* branches, are adopted.

Despite the rigor and success of this process, it is often considered outdated. Izquierdo-Cortazar et al. (2017) [8] advocate for modernizing the review system, citing the limitations of mailing lists: contributors must proactively subscribe to them, and issues related to email delivery to subscribers are common. Solutions like the Lore kernel archives and *GitGadget* attempt to mitigate these problems by offering web-based access to mailing lists and enabling contributions via *GitHub Pull-Requests*, respectively. These efforts underscore the growing demand for a more accessible and efficient development workflows without compromising the collaborative, decentralized nature of the project.

### 2.3 The Linux kernel development model

The Linux kernel development model encompasses a wide range of *workflows* that go beyond technical implementation. These include submitting patches to mailing lists, following subsystem-specific guidelines, and adhering to strict release cycles. While essential to maintaining structure and quality, these workflows expose bottlenecks that limit efficiency. As noted by Corbet and Kroah-Hartman (2017) [4], tooling is critical for managing the complexity of a project as large and distributed as Linux, stating that “Without the right tools, a project like the kernel would simply be unable to function without collapsing under its own weight.” Git is an example of a tool devised in the Linux development context back in 2005, also created by Linus, to replace the previous *Version Control System* (VCS) used, and it has since become a cornerstone of modern software development.

The community has developed and maintains various tools to cope with workflow challenges. These range from official scripts, like *get\_maintainers.pl* (used to identify appropriate recipients for patches), to standalone projects, such as *b4* (used for retrieving patches from archived mailing lists). Developers also create *ad-hoc* scripts to address specific personal issues, often resulting in

duplicated efforts and a lack of standardization. To contribute to the scenario, we are actively developing Free Software tools such as *kworkflow* [14] (kw) and its subproject *patch-hub* [15], aiming to centralize and streamline development workflows through a unified interface. These tools seek not only to reduce inefficiencies but also to enhance the developer experience sustainably and collaboratively.

### 3 Research Design

The Linux kernel project presents a unique organizational structure and a set of collaborative development practices. However, as discussed in the previous sections, it also reveals structural challenges and recurring bottlenecks that may hinder its efficiency and long-term sustainability. These issues motivate our research, which combines empirical methods with tool-supported interventions grounded in the realities of kernel development. In this sense, we present the two primary objectives of this work:

**Objective 1.** : Validate a theoretical framework that accurately describes the overarching workflows of the Linux kernel development model and allows us to identify bottlenecks.

**Objective 2.** : Develop Free Software tools that efficiently mitigate bottlenecks in the Linux kernel development model using informed decisions based on a validated theoretical framework.

. To guide the research work needed to accomplish these objectives, we designed our study around the following two main research questions (RQs):

**RQ.1:** *What overall workflows compose the Linux kernel development model?* This question aims to identify and characterize the workflows that sustain the Linux kernel development process. These workflows comprise technical and social processes and practices, from compiling and installing a kernel from source code to patch submission and subsystem-specific conventions. By answering RQ.1, we seek to build a comprehensive and structured understanding of how development activities are coordinated across the ecosystem.

**RQ.2:** *Which processes and/or practices generate bottlenecks in the Linux kernel development model that compromise its efficiency and scalability?* Building on the workflows mapped in RQ.1, this question investigates the critical points where coordination, review, or tool limitations slow development and reduce productivity. The aim is to uncover systemic inefficiencies and understand how they impact maintainers, contributors, and the overall project governance.

**RQ.3:** *Which bottlenecks can be mitigated by streamlining processes through automation?* This subquestion explores opportunities for improving the development experience by automating repetitive and/or error-prone tasks. We examine whether automation can reduce delays, lower entry barriers for contributors, or alleviate maintainer overload, thereby increasing scalability and sustainability.

### 3.1 Research methods

This study adopts a multi-method qualitative approach combining two complementary methods: (i) Ethnographic Case Studies (including participant and non-participant observation) and (ii) a Multivocal Literature Review (MLR).

**3.1.1 Ethnographic case studies.** Ethnographic case studies provide an in-depth, context-sensitive understanding of practices within a particular setting, combining methods such as observation, interviews, and document analysis [5]. In our study, this approach draws on both direct involvement in the Linux ecosystem (*participant observation*) and interactions with contributors and documentation analysis without direct engagement (*non-participant observation*).

For instance, we are conducting participant observation, interacting and contributing (sending patches) with AMD GPU and IIO (Industrial I/O) subsystems. The goal is to document experiences, interactions, and challenges in a contribution journal. In parallel, we maintain two ongoing side projects, kw and patch-hub, as additional sources of insights into kernel workflows and tool-supported processes and practices.

We are also investing in non-participant observation comprised of three complementary strategies:

- (1) **Mentoring newcomers:** Support and observe new contributors, cataloging experiences from the mentors' and mentorees' perspectives;
- (2) **Empirical trials:** Conduct experiments with newcomers and experienced developers to evaluate how the proposed tools support workflows and mitigate bottlenecks. Newcomer feedback will be gathered through questionnaires; data from veteran developers will be collected via interviews and anonymized telemetry, following the model of the *Debian Popularity Contest*<sup>2</sup>;
- (3) **Community engagement:** Participate in key community events to interact with core developers and gather qualitative feedback, as the Linux Foundation Technical Advisory Board (TAB) recommended to our research group regarding how we should approach collecting feedback from the Linux community.

**3.1.2 Multivocal Literature Review (MLR).** The MLR complements the ethnographic case studies methods by synthesizing evidence from academic literature and Grey Literature (e.g., blogs, mailing lists, conference talks). It combines the rigor of Systematic Literature Review (SLR) with the breadth of Grey Literature Review (GLR) [6]. Building on Wen's earlier MLR [16], we are conducting an updated review focused on development workflows in the Linux kernel. This review supports triangulation, allowing us to compare empirical findings with academic and practitioner perspectives to reduce bias and strengthen the study validity.


**3.1.3 Grounded Theory (GT).** In **Objective 1**, we aim to validate a taxonomy using *Grounded Theory* (GT). This method builds structured classifications from empirical data [7], widely adopted in software engineering [10]. The taxonomy will categorize macro workflows in Linux kernel development, possibly including nested

<sup>2</sup>Debian Popularity Contest website.

subcategories for detailed analysis. Through iterations, it is expected to evolve into an *emergent theory* - a coherent framework that offers more profound insights into the complexities and workflows of the Linux kernel development model.

## 4 Phases and Current Progress

This work combines two research methods and the concurrent development of Free Software tools. **Figure 2** summarizes the four planned phases of our research. Each phase comprises activities (such as workflow mapping or tool development) centered around a core theme. All phases culminate in an iteration of our theoretical framework for the Linux workflows while leveraging these refined iterations to make informed decisions on the development of the aforementioned tools. At the time of writing, Phase 1 has been completed, while Phases 2 and 3 are ongoing.



**Figure 2: Description of the research work in phases.**

### 4.1 Phase I: Exploratory immersion

This phase focused on engaging with the Linux kernel ecosystem, mentoring newcomers, and developing kw and patch-hub.

*P1.1: Exploration of the Linux ecosystem.* We engaged with the ecosystem by submitting exploratory patches to subsystems like AMD GPU, IIO, and staging. We also studied the experiences of other contributors through blogs, papers, and direct conversations.

*P1.2: Mentoring newcomers I.* In early 2024, during our *Free Software Development* course, we mentored about 30 students through setting up a development environment, developing a patchset, sending it as a contribution, and participating in the review process of Linux. This approach included in-person workshops with veteran developers. Students completed an anonymous survey and wrote blog posts to report their experiences.

*P1.3: Tools development I.* We actively developed kw and mentored two contributors through *Google Summer of Code* (GSoC). patch-hub was extracted from kw, rewritten in Rust, and evolved into a standalone project with improved performance and stronger community engagement.

### 4.2 Phase II: Deeper immersion

In this phase, we aim for deeper technical involvement and to introduce controlled experiments with newcomers.

*P2.1: Deeper contributions and maintainer role.* We are submitting more impactful patches and participating in code reviews to simulate maintainer responsibilities. We aim to escalate our involvement in the ecosystem naturally.

*P2.2: Mentoring newcomers II.* A second iteration of the mentoring course is being offered in 2025, incorporating lessons learned from the first edition.

*P2.3: Experiments I (newcomers).* During the second iteration of the mentoring course, half the students were randomly assigned to use kw, while the rest used the original (unassisted) toolset. A survey is being used to collect data to validate the hypothesized workflow bottlenecks and measure if and how kw mitigated them, both qualitatively and quantitatively.

*P2.4: Tools development II.* With clearer insights into workflows, kw is being stabilized, and patch-hub is being expanded. We are mentoring another contributor through GSoC 2025, focusing on patch-hub improvements.

### 4.3 Phase III: Unbiasing through external validation

This phase cross-validates findings from previous phases with external sources to reduce bias.

*P3.1: Multivocal Literature Review.* We are conducting an updated MLR focused on kernel development workflows, combining academic publications and grey literature such as blogs and mailing lists.

*P3.2: Community feedback at events.* Following the recommendation from the Linux Foundation TAB, we are participating in events such as *FOSDEM 2025*<sup>3</sup> and *DebConf 2025*<sup>4</sup>, ideally as speakers presenting kw and patch-hub to collect direct feedback from experienced kernel developers and key personnel of the community.

*P3.3: Tools development III.* We will refine the tools based on insights from the first iteration of our taxonomy and community feedback.

### 4.4 Phase IV: Final validation in real-world scenarios

The final phase aims to validate the improved taxonomy through experiments with experienced kernel developers.

*P4.1: Experiments II (veteran developers).* Veteran developers will use kw and patch-hub in their regular workflows. Usage data will be collected via kw data collection (e.g., compilation frequency and duration) and local storage infrastructure. This collected data will be sent to servers using its telemetry features and analyzed. A data anonymization mechanism inspired by the *Debian Popularity Contest* is being designed.

*P4.2: Tools development IV.* Based on the refined taxonomy from earlier phases, we will finalize tool development to align with real-world kernel development practices.

<sup>3</sup>FOSDEM 2025

<sup>4</sup>DebConf 2025




## 5 Preliminary Results and Discussion

In this section, we present and discuss the early results of our research work.

### 5.1 Empirical evidence of long-term unsustainability

We have produced empirical quantitative evidence indicating that the Linux kernel development model may be unsustainable due to its current structure<sup>5</sup>. **Figures 3, 4, and 5** are plots that show statistics about the development of Linux over the last 10 years. Due to the periodicity of releases that follow subsequent six to eight-week cycles, we can use the Linux versions as consistent timestamps to analyze the evolution of the project. In this sense, the aforementioned figures have the Linux versions in the abscissa from 3.19 (launched on 8 February 2015) until 6.13 (launched on 20 January 2025).




**Figure 3: Linux logical Lines of Code (LLOC) from version 3.19 to 6.13.**

**Figure 3** displays the increase of *logical Lines of Code (LLOC)*<sup>6</sup> and shows how the Linux kernel code base is steadily growing regarding its size. We can derive that the project complexity is also growing as more features, drivers, and the like are continuously being merged. Interestingly, by investigating the entries in the MAINTAINERS file, we produced **Figure 4** that depicts how the number of maintainers steadily increases.

Notwithstanding the increase in the number of maintainers, we can see in **Figure 5** that the amount of commits in each development cycle of Linux fluctuates between 13000 and 17500 since version 3.19, excluding outliers. Every commit is different as an individual commit can be a massive change, while a set of ten commits can be a single line change ten times, and a difference of four and a half thousand commits is expressive, so we can not derive solid conclusions based on these statistics. However, just the fact that the number of commits has fluctuated consistently indicates that the contribution throughput does not scale in the same fashion as the number of maintainers. We can hypothesize that, as time passes, parts of the code base do not receive maintenance for long periods,


<sup>5</sup>These experiments are reproducible with *Docker* following the instructions in the git repository pointed in the *Artifacts Availability* section.

<sup>6</sup>A software metric that measures the number of source lines of code (excluding blank ones and comments) in a program source code.



**Figure 4: Number of Linux maintainers from version 3.19 to 6.13.**

either because they are abandoned or have reached great stability; no matter the case, this would still incur in the growing proportion of maintainers per LLOC (in this scenario, LLOC would, at least, not grow accordingly) not translating in more code productivity.




**Figure 5: Commits in the development cycle of versions 3.19 to 6.13.**

The Linux kernel development model functions as a self-sustaining and highly specialized ecosystem. However, by extrapolating the empirical evidence, we can assume that the model reliance on a continuous influx of skilled contributors, a highly dedicated pool of maintainers, and ever-increasing code complexity can indicate long-term sustainability risks<sup>7</sup>.


### 5.2 Core overall workflows

We have extensive experience with the Linux ecosystem from both industry and academic perspectives. By actively contributing to and even assuming maintainer responsibilities in subsystems such as *AMD GPU*, *Industrial I/O (IIO)*, and *Virtual Kernel Mode Setting (VKMS)*, along with conducting research in Free Software, in special, Linux, many insights emerge.

<sup>7</sup>We are currently designing a platform to provide a more comprehensive and in-context view of data points about Linux development and give a better foundation to our claims of unsustainability.



**Figure 6: Concept map of the patchset development workflow.**



**Figure 7: Concept map of the patchset reviewing workflow.**

Building from those, the work done in Phase 1 (as described in **Section 4.1**) formalized the two core overall workflows, which are the *patchset development workflow* (**Figure 6**) and the *patchset reviewing workflow* (**Figure 7**) as concept maps. The former relates to contributors' work, while the latter relates to maintainers' work.

Due to the vastness and diversity of the Linux subsystems, these workflows can mutate depending on the context-specific needs and characteristics; as such, we denominate them as *overall*.

### 5.3 Development of supporting tools

Drawing from the same sources as the previous section, we developed kw, a *Developer Automation Workflow System* (DAWS) designed to streamline and automate workflows for Linux developers. It provides a unified interface offering solutions to common kernel development challenges, such as abstracting hardware and distribution-specific complexities for tasks like configuring, compiling, and installing custom kernels. It also includes tools for submitting contributions and managing reviews, which have gained traction among industry developers. We also developed patch-hub, a *Terminal User Interface* (TUI), designed for maintainers, that simplifies the interaction with patches sent to mailing lists and review management, addressing one of the most critical bottlenecks in the development model.

From the users' perspective, kw is built as a hub-like tool that provides a set of commands covering many aspects of the kernel workflows. For instance, there are commands to streamline and automate the tasks of compiling and installing a kernel from the source code, as well as commands to manage configuration files, target machines, and much more. Even though we singled out patch-hub throughout the text, it still is a command of kw, only with the distinctive characteristic of being a dedicated sub-project with a different software stack and more abrangent scope, compared with the other commands.

From the developers' perspective, kw can still be viewed as a hub due to its modularized and extensible architecture incorporating robust existing tools that already solve Linux developers' pain points. In this regard, the project suppresses duplication of efforts while providing high-quality solutions to users and enhancing maintenance for its developers.

kw also has a comprehensible and extensible infrastructure to (locally) collect data points that could be of interest for research into the workflows of the Linux kernel development model. For example, the time of compilation and whether it was successful is currently collected by kw and can be used to derive results about the compilation of the kernel task. Another interesting data point regarding compilation could be hardware setups and cross-compilation tracking, allowing for deep analysis of the efficiency of hardware setups and compiler use.

## 6 Conclusion

This paper presents an ongoing effort to understand and support the sustainability of the Linux kernel, an essential Free Software project in Computer Science and beyond. Given its complexity and scale, we propose a research plan combining empirical and non-empirical methods to: (1) develop a theoretical framework for its development workflows, and (2) design tools to address identified bottlenecks. Preliminary findings suggest concerns about scalability and long-term sustainability. Observations reveal variations and inefficiencies across subsystems, motivating deeper analysis. The emerging framework serves as an analytical tool and a foundation for practical interventions, aiming to bridge gaps between research and practice. By sharing this work-in-progress, we invite feedback from the Software Engineering community and aim to spark discussion on sustaining large, community-driven Free Software projects. Insights from the kernel can guide tool development and future research.

## ARTIFACT AVAILABILITY

To reproduce the experiments that generated the Linux project statistics, visit **this Software Heritage permalink**, then follow the instructions described in the file `README.md`. The only requirements to run these experiments are to have docker and docker-compose installed.

## ACKNOWLEDGMENTS

This study was financed, in part, by CAPES (Finance Code 001), the University of São Paulo – USP (Proc. 22.1.9345.1.2), the São Paulo Research Foundation – FAPESP (Proc. 19/26702-8) and the São Paulo State Data Analysis System Foundation – SEADE (Proc. 2023/18026-8), Brazil.

## REFERENCES

- [1] Jonathan Corbet. 2014. *How 4.4's patches got to the mainline*. Linux Weekly News. <https://lwn.net/Articles/670209/>
- [2] Jonathan Corbet. 2017. *Patch flow into the mainline for 4.14*. Linux Weekly News. <https://lwn.net/Articles/737093/>
- [3] Jonathan Corbet. 2021. *Finding real-world kernel subsystems*. Linux Weekly News. <https://lwn.net/Articles/844539/>
- [4] Jonathan Corbet and Greg Kroah-Hartman. 2017. *Linux Kernel Development Report*. Linux Foundation. <https://www.linuxfoundation.org/resources/publications/linux-kernel-report-2017?hsLang=en>
- [5] W. Edmonds and Thomas Kennedy. 2017. *An Applied Guide to Research Designs: Quantitative, Qualitative, and Mixed Methods*. SAGE Publications, Inc, USA. doi:10.4135/9781071802779
- [6] Vahid Garousi, Michael Felderer, and Mika Mäntylä. 2018. Guidelines for including grey literature and conducting multivocal literature reviews in software engineering. *Information and Software Technology* 106 (09 2018).
- [7] Barney Glaser and Anselm Strauss. 2017. *Discovery of grounded theory: Strategies for qualitative research*. Routledge, USA.
- [8] Daniel Izquierdo-Cortazar, Nelson Sekitoleko, Jesus M. Gonzalez-Barahona, and Lars Kurth. 2017. Using Metrics to Track Code Review Performance. In *Proceedings of the 21st International Conference on Evaluation and Assessment in Software Engineering (Karlskrona, Sweden) (EASE '17)*. Association for Computing Machinery, New York, NY, USA, 214–223.
- [9] Greg Kroah-Hartman. 2016. *Kernel Recipes 2016 - Patches carved into stone tablets*. Linux Kernel community. <https://github.com/gregkh/presentation-stone-tools/tree/master> Licensed under CC BY-NC-SA 4.0. Image modified by adding the overlaying rectangle with the “contributor-maintainer interface” text.
- [10] Leonardo Alexandre Ferreira Leite, Paulo Roberto Miranda Meirelles, and Fábio Kon. 2022. *A grounded theory of organizational structures for development and infrastructure professionals in software-producing organizations*. Ph.D. Dissertation. University of São Paulo.
- [11] Nicolas Palix, Suman Saha, Gaël Thomas, Christophe Calvès, Julia Lawall, and Gilles Muller. 2011. Faults in Linux: Ten Years Later. *ACM SIGARCH Computer Architecture News* 39 (03 2011).
- [12] Peter C. Rigby, Daniel M. German, Laura Cowen, and Margaret-Anne Storey. 2014. Peer Review on Open-Source Software Projects: Parameters, Statistical Models, and Theory. *ACM Trans. Softw. Eng. Methodol.* 23, 4, Article 35 (Sept. 2014), 33 pages. doi:10.1145/2594458
- [13] Abraham Silberschatz, James L. Peterson, and Peter B. Galvin. 2008. *Operating System Concepts*. Addison-Wesley Longman Publishing Co., Inc., USA.
- [14] Rodrigo Siqueira, David Tadokoro, and Matheus Tavares. 2025. *Kworkflow*. University of São Paulo. <https://archive.softwareheritage.org/swh:1:dir:90dc41328e09271597eb1f4f47d8a4c2e972a5bb;origin=https://github.com/kworkflow/kworkflow;visit=swh:1:snp:4e47e956d8c04a55836d674aedf3c7be842b2641;anchor=swh:1:rev:e1ac9a1965c366e200f9ab242a89a6545adcc7cc> Archived in Software Heritage: swh:1:dir:90dc41328e09271597eb1f4f47d8a4c2e972a5bb.
- [15] David Tadokoro, Lorenzo Salvador, and Rodrigo Siqueira. 2025. *Patch-Hub*. University of São Paulo. <https://archive.softwareheritage.org/swh:1:dir:23424ae7165f4c170f860c4cd05a63ff2bcad75d;origin=https://github.com/kworkflow/patch-hub;visit=swh:1:snp:ab91604e24b4702302d8191186222509eb4b766a;anchor=swh:1:rev:deba3897e5dc0f07073146734ac16f723e60367d> Archived in Software Heritage: swh:1:dir:23424ae7165f4c170f860c4cd05a63ff2bcad75d.
- [16] Melissa Shihfan Ribeiro Wen. 2021. *What Happens When the Bazaar Grows: A comprehensive study on the contemporary Linux kernel development model*. Master's thesis. University of São Paulo.